

MILS-700

MEDIUM IN-LINE SYSTEM

eilit
A **Controlar** company



Distributed by



MAXIM SMT
ADAPT - AUTOMATE - ASSEMBLE

MILS Handler Series:

Precision, Versatility, and Cost-Efficiency for Advanced In-Line Testing

The MILS handler series is prepared for the most demanding applications.

Designed to your exact needs for flashing (ISP) and funtional (FCT) aplications, large panels and future expandability.

Wide range of PCB dimensions, high handling speed, fast and easy setup, facilitated product changeover, flexible and adapted to different electronic test technologies, the MILS will be the best choice for your in-line testing needs.

MILS-700

MILS-700 is a **versatile in-line handler** designed for global integration of instrumentation. It supports manufacturer such Teradyne, Keysight, Checksum, TRI, and others.

- Fast and ergonomic fixture exchange
- Small footprint – other modules may be pressed against both sides
- Lateral actuation for DUT connectors (USB, Ethernet, etc.) with controlled insertion force

We encourage the constant **exchange of ideas and best practices** with our customers and partners. Our projects provide **optimal** solutions for specific test needs integrated in our **in-line Handling Systems**.

Features

- High resistance iron and aluminum structure to handle up to 8 KN forces
- Automatically adjustable conveyor width with programmable memory settings
- High speed conveyor with programmable speed up to 1000 mm/s
- Pneumatic system compression
- Dual Stage testing
- Compatible with XILS-600 and ILS-700 fixture kit
- Handling time approx. 5 seconds (machine cycle time excluding test)
- Less than 3 minute fixture changeover time
- Fixture Coding on both Bottom and Top plates for product/fixture validation
- Modular pylon blocks for integration of instrumentation such as CAN, RF, pneumatic or other specific needs
- Machine Control communication drivers for .NET, NI LabWindows CVI, LabVIEW or any other third-party platforms with TCP/IP communication sockets
- Beckhoff virtual PLC with HMI



MILS-700

Max. TP (bottom+top)
Max. probe force
Max. fixture top/bottom (transfer pins)
Max. PCB component height (Bottom side)
Max. PCB component height (Top side)
Min. PCB border without components
Max. PCB size
Min. PCB width
Handler Specifications
Length
Width
Height
Weight
Conveyor max. width
Conveyor min. width
Transportation height
Handling time (machine cycle)
Max. conveyor speed
Max. top plate speed
Conveyor movement direction
Electrical requirements
Pneumatic requirements
Fixture exchange time
Machine communication
Rackeable/Instrumentation space
Interface type
CE approved

1000
8 Kn
500
50 mm
100 mm
5 mm
1 X (510 X 350 mm) o 2 X (245 X 350 mm)
60 mm
700 mm
1200 mm
1650 mm
500 kg
350 mm
60 mm
930 + 40 mm
Approx. 5 sec
1000 mm/s
120 mm/s
Left > Right / Right > Left
1x220V AC 50-60Hz
5 – 7 Bar
<3 min
Sockets communication
10 U
Pylon Block
Yes



Innovation, Quality and **Passion for Engineering.**



A **Controlar** company

EIIT SA.

Camino Robledo de Chavela, 9-B
28210 Valdemorillo - Madrid
Spain

+34 91 890 46 14
info@eiit.com
www.eiit.com



01 PORTUGAL | **02** SPAIN | **03** MEXICO | **04** GERMANY | **05** INDIA | **06** MALAYSIA | **07** CHINA | **08** USA

Distributed by



MAXIM SMT
ADAPT - AUTOMATE - ASSEMBLE

Plot No.78 A
Sector-5, IMT Manesar,
Gurgaon-122050, Haryana
India

www.maximsmt.com
sales@maximsmt.com
Tel +91-124-4354974-75



MAXIM
PRECISION TECHNOLOGIES
A **Controlar** JV company

Test Systems ■ Automation Solutions

Plot No. PAP-K-27
Phase II, MIDC Chakan, Industrial Area
Savardari Taluka Khed
Pune - 410501, Maharastra
India

www.maximpt.net
sales@maximpt.net

24 x 7 Help Line
+91-8826625406